

UV-c clarifiers selection table



Type	Unit	VarioClean S 18	VarioClean S 36	VarioClean Pro 36	VarioClean Pro 55	VarioClean Pro 75	VarioClean Pro-X 120	VarioClean Pro-X 190	VarioClean Pro-X 285
Flow capacity max	m ³ /hour	3	6	10	15	20	25	50	75
Flow capacity recommended	m ³ /hour	3	6	6	9	12.5	Project dependent	Project dependent	Project dependent
Advised pond volume - water only	m ³	6	12	12	18	25	70	100	170
Advised volume - swimming pond	m ³	●	●	12	18	25	45	70	120
Advised volume - plant pond	m ³	15	27	27	42	60	80	130	210
Advised volume - fish and plant pond	m ³	9	18	18	28	40	55	80	135
Advised pond volume - koi carp	m ³	●	●	12	18	25	35	50	85
Dimensions l x w x h	cm	36 x 16 x 11.5	55 x 16 x 11.5	52 x 18 x 15	64 x 18 x 15	96 x 18 x 15	30 x 30 x 69	30 x 30 x 69	30 x 30 x 69
Material		Plastic ASA Stainless steel 304	Plastic ASA Stainless steel 304	Plastic ASA Stainless steel 316L	Plastic ASA Stainless steel 316L	Plastic ASA Stainless steel 316L	Stainless steel 316L	Stainless steel 316L	Stainless steel 316L
Voltage	Volt/Hz	230/50	230/50	230/50	230/50	230/50	230/50	230/50	230/50
Power consumption	Watt	22	40	40	60	80	140	200	300
Lamp wattage	Watt	18	36	36	55	75	2 x 60	2 x 95	3 x 95
Connections	Inches "	1½	1½	1½	1½	1½	3	3	3
Power cable	m	5	5	5	5	5	2	2	2
Max. pressure	Bar	1	1	1	1	1	2	2	2
Built-in micro-switch, switches lamp off when opened		✓	✓	✓	✓	✓	✓	✓	✓
Connection pieces supplied		2x Hose connections 20/25/32/40 mm	2x Hose connections 20/25/32/40 mm	2x Hose socket 32/40/50 mm 2x Solvent union 50/63/75 mm	2x Hose socket 32/40/50 mm 2x Solvent union 50/63/75 mm	2x Hose socket 32/40/50 mm 2x Solvent union 50/63/75 mm	●	●	●
Article number		202011	202012	202036	202055	202075	202020	202021	202022
Warranty (except quartz glass and uv-c lamp)	Years	2	2	2	2	2	2	2	2

✓ Yes/suitable ● No/unsuitable

More info: www.auga.nl